

MADE IN GERMANY



Forming tools with 16 profile shapes.
FUGI II with guiding aid!

FUGI KIT


SILICONE PROFILING TOOL

Intersection:

FUGI II (orange): To cross over intersecting grout lines, push both sliding pieces diagonally into the designated guides.

FUGI (blue): Cover one grout with masking tape. This way, you can cross over the other one.

Cleaning of FUGI: Wipe the excess sealant off the FUGI with household paper towel. Should this be forgotten, simply rub the tool across a rubber-like surface.

Removal of old grouts: Remove old caulking carefully with a caulking removal knife with saw blade. Whatever is left on tiles or other smooth surfaces can be removed with a scraping blade. On soft surfaces a scraping blade could scratch, it's better to use here a chemical silicone remover.

Important: When removing old mildew stained grouts or caulks, wear a protective mask (to avoid the danger of infection). Use an anti-mildew treatment on the affected area. Be sure the surface you work on is dry and free of oil or grease before restart caulking.

Made in Germany by:
 Cramer GmbH | Salzstr. 8A | 85622 Feldkirchen
 Tel. +49 (0)89 99909 770
 www.drybathrepair.com
 No. 40405

The FUGI Kit helps to achieve clean profiles and provides for a permanent seal.

A releasing agent (soapy water) is not needed to apply the soft caulking mass (silicone). This process results in better adhesion and prevents mould from forming underneath. In the event that the profile application is not perfect, it is possible to redo isolated parts without removing the entire profile.

What kind of sealants?

Silicone, acrylic, polyurethane... actually all sealants may be applied: sealing and flexible grouts can be made with our FUGI.

What kind of surfaces?

FUGI can be used on all smooth, rough or uneven surfaces. However, working on extremely rough surfaces will wear out your FUGI faster!


How to use:

Choose the caulking line shape from 16 profile possibilities.

Apply appropriate amount of caulking mass on a distance of 60-120cm (it is easier to work step by step, by only applying material for short distances). Make sure both FUGI edges touch both surfaces. Slightly press the FUGI and pull.

Important: Always use the smooth FUGI edge for spreading.

Regard the spreading-direction!



Start again behind the position at which you stopped with a new line section.

Bridging across a vertical grout:

FUGI II (orange): To cross one-sided grout lines, push the sliding piece diagonally to the FUGI II into the guides provided.

FUGI (blue): If you hold the FUGI at a slight angle, you cross over the grout-line and doing so you will keep a uniform grout-pattern profile.

Corners: Start first with the vertical wall-grout lines and let them bond. After bonding, you work on the floor-grout starting out of the corners in both directions.